

A Fuel Cell Based Four-Phase Interleaved Step-down Converter with Uniform Current Sharing and high step-down ratio

Bodisetty Ramanjulu, A. Ravi Kumar, D. Prasada Rao ¹M. Tech Student Department of PE ELLENKI College of E&T ^{2,3} Associate professor Department of EEE ELLENKI College of E&T

Abstract

A Novel Fuel Cell based transformer less interleaved high step-down conversion ratio dc-dc converter with low switch voltage stress has been presented. In this converter, two input capacitors are series-charged by the input voltage and parallel discharged by a new twophase IBC for providing a much higher stepdown conversion ratio without adopting an extreme short duty cycle. Based on the capacitive voltage division, the main objectives of the new voltage-divider circuit in the converter are both storing energy in the blocking capacitors for increasing the stepdown conversion ratio and reducing voltage stresses of active switches.

As a result, the presented converter topology possesses the low switch voltage stress characteristic. This will allow one to choose lower voltage rating MOSFETs to reduce both switching and conduction losses, and the overall efficiency is consequently improved. Moreover, due to the charge balance of the blocking capacitor, the converter features automatic uniform current sharing characteristic of the interleaved phases without adding extra circuitry or complex control methods. Here interleaved buck converter and its operation are discussed. Also comparisons with conventional interleaved buck converter and simulation results are included.

1.INTRODUCTION

Nowadays high performance dc – dc converters are required for increasing high stepdown conversion ratio with high output current applications like CPU boards and battery chargers, and distributed power systems [2] – [4]. For non-isolation applications with low output current ripple requirement, an interleaved buck converter (IBC) has received a lot of attention due to its simple structure and low control complexity.

Interleaving technique connects dcdc converters in parallel to share the power flow between two or more conversion chains it implies a reduction in the size, weight and volume of inductors and capacitors. Also a proper control of the parallel converters increase the ripple frequency and reduces the ripple waveforms at the input and output of the power conversion system, which leads significant reduction of current, voltage ripples and filter



capacitor size. Therefore the interleaved buck converters has received a lot of attention in nonisolation applications with low output current ripples.

However. in the conventional multiphase IBC, as shown in active switches are required to use high-voltage devices that are rated above the input voltage. High-voltagerated devices generally render a number of undesirable characteristics, such as high cost, large on-resistance, large voltage drop, and severe reverse recovery. For high-input lowoutput voltage regulation applications, operations at higher switching frequencies are required to achieve a higher power density and better dynamics [5]. However, the buck converter with a high step down conversion rate yields a significant switching loss due to its extremely low duty cycle. This fact not only limits the achievable switching frequency, but also complicates its implementation. In addition, the efficiency is further compromised due to the short on- time and long freewheeling time within each switching cycle [6].

To overcome such disadvantages of the conventional IBC, a number of modified IBC structures have been proposed [7]–[14]. A multiphase IBC with extended duty ratio [7], [8]was proposed for high-input low-output voltage regulation applications. Two and fourphase versions of the topology were examined in [7] and [8]. The four-phase extended duty ratio IBC The mechanism of the extended duty ratio lies in the use of highly efficient input voltage dividers which reduce the switching voltage and the associated losses. However, the voltage stress to input switching devices remains rather high.

In this paper, we propose a novel transformer -less dc converter that features low switch voltage stress and automatic uniform current sharing. An interleaved four-phase voltage divider is used to achieve a high stepdown conversion ratio. In the proposed converter, series charging of the two capacitors from the input voltage and parallel discharging to the load facilitated by a new four phase IBC. This architecture provides a high step-down conversion ratio and a low output current ripple without requiring an extremely low duty cycle. Based on the capacitive voltage division, the new voltage-divider circuit in the converter achieves two major objectives, i.e., increased voltage conversion ratio, due to energy storage in the blocking capacitors, and reduced voltage stress of active switches. The low switch voltage stress offered by the proposed converter topology allows the use of lower voltage rating MOSFETs to reduce both switching and conduction losses, thereby improving the overall efficiency. Moreover, due to the charge balance of the capacitors, the converter features automatic uniform current sharing of the without interleaved phases adding extra circuitry or complex control methods.



International Journal of Research Available at <u>https://edupediapublications.org/journals</u> e-ISSN: 2348-6848 p-ISSN: 2348-795X Volume 04 Issue-17 December 2017

2. NOVEL TRANSFORMER-LESS FOUR PHASE BUCK CONVERTER

The proposed converter is shown in Fig. 1, which is derived from the two-phase IBC with an extended duty ratio in [9]. In order to further reduce the output current and output voltage ripples, the converter is divided into four-phase small inductors via an interleaved operation. It is clear from Fig. 1 that the proposed converter consists of four inductors, four active power switches, four diodes, and four capacitors. The proposed converter topology with low switch voltage stress and high step down ratio can only be achieved when the duty cycle is lower than 0.5 and operated in CCM. In addition, when the duty cycle is lower than 0.5, due to the charge balance of the blocking capacitor, the converter enables automatic current sharing so as to obviate any extra current-sharing control circuit. On the other hand, when the duty cycle is higher than 0.5 or when the converter is operates under DCM with a light load, the converter no longer possess the automatic current-sharing capability, and the current-sharing control between each phase should be taken into account.



Fig 1. Circuit Diagram of Proposed IBC

3.MODES OF OPERATION

In order to clearly explain the operation principle, the operating duty ratios 0 < D < 0.25 and 0.25 < D < 0.5 by the proposed four-phase and two-phase interleaved strategies are, respectively, introduced. Referring to the gate signals shown in Fig. 2, the corresponding operating modes of the proposed converter for condition 0 < D < 0.25 is discussed next. In first mode, switch S1 is turned on, and switches S2, S3, and S4 are all OFF. Hence, diode D1 becomes OFF whereas diodes D2, D3, and D4 remain ON. The stored energy of C1 is discharged to CA, L1, and the output load, whereas current iL2, iL3, and iL4 are freewheeling through D2, D3, and D4, respectively. In the next mode all switches gets off. In this case, iL1, iL2, iL3, and iL4 are freewheeling through diodes D1, D2, D3, and D4, respectively .In next mode only S2 gets on an all others off. Corresponding changes as in mode 1 continues.





Fig 2. Gate Pulse of four phase strategy

Referring to the gate signals shown in Fig. 3, In first mode two switches S1 and S2 gets on It is observed that iL3 and iL4 are freewheeling through D3 and D4, respectively, and L3 and L4 are releasing energy to the output load. The stored energy of C1 is discharged to CA, L1, and the output load, while the stored energy of CB is discharged to L2 and the output load. In the next mode all switches are off. In this case, iL1, iL2, iL3, and iL4 are freewheeling through diodes D1, D2, D3, and D4, respectively. During next mode other pair of switches gets on and current flow continues.



Fig 3. Gate Pulse of two phase strategy

4.DESIGN

From the volt-second relationship on inductors L1 - L4, it is obtained as $(V_{C1} - V_{CA} - V_0)D - V_0(1 - D) = 0$ $(V_{CB} - V_0)D - V_0(1 - D) = 0$ $(V_{C2} - V_{CB} - V_0)D - (1 - D)V_0 = 0$ $(V_{CA} - V_0)D - (1 - D)V_0 = 0$ From the above equation , it can be derived as

$$MStep-down = \frac{Vo}{Vin} = \frac{D}{4}$$

The components are designed based on the assumption that all components are ideal, the capacitors are large enough that the voltage across them can be considered as constant also C1=C2 and CA =

$$CB. Vo = \frac{D}{4} \times Vin$$

$$1 = 2 = L3 = L4 = \frac{VoTs(1-D)}{\Delta IL}$$

$$C_{A} = C_{B} = C1 = C2 = \frac{\Delta ILDTs}{\Delta IL}$$

$$C_{O} = \frac{\Delta IL}{8(\Delta Vo - \Delta IL * ESR) fs}$$

5.SIMULATION RESULTS

The closed loop Simulation of the above converter is done in MATLAB simulink using 400 V input and 24 V, 500 W output at 40 KHZ frequency. The Parameters used in Simulation are shown in Table 1 Table 1. Parameters Used in Simulation

Sl.No	Paramers Used	Specification
1	Inductors	250µH
2	Capacitors CA,	10µH
	CB,C1,C2	
3	Output Capacitor	220µH
	Co	



International Journal of Research

Available at https://edupediapublications.org/journals

e-ISSN: 2348-6848 p-ISSN: 2348-795X Volume 04 Issue-17 December 2017

4	Output Resistor	1.152Ω
5	Duty Ratio	24
6	Output Power	500 W
7	Frequency	40KHz
8	Input Voltage	400V
9	Output Voltage	24 V

12 SIMULATION RESULTS



Fig 4. Simulation Diagram of Fuel Cell based IBC



Fig 5. Simulation diagram of fuel cell subsystem.



Fig 6. Wave forms of interleaved extension of IL1, IL2, IL3, IL4.



Fig 7. Wave forms of Interleaved extension in voltage stress V_{DS1, 2, 3, 4}, (10 μS/div)



Fig 8. Wave forms of interleaved extension in Voltage stress V_{D1, 2, 3, 4},(10 μs/div).



International Journal of Research

Available at https://edupediapublications.org/journals

e-ISSN: 2348-6848 p-ISSN: 2348-795X Volume 04 Issue-17 December 2017



Fig 9. Wave forms of Inter leaved extension gate signals in V_{GS1, 2, 3, 4}.



Fig 10. Output Voltage & Current wave forms of interleaved extension.



Fig 11. Wave forms of interleaved in $I_{L1,\,2,\,3,\,4.}$



Fig 12. Wave forms of interleaved in V_{D1, 2, 3, 4} ,(10 $\mu s/div$).



Fig 13. Wave forms of interleaved voltage stress $V_{DS1, 2, 3, 4}$ (10 μ s/div).





Fig 14. Wave forms of interleaved voltage gate







6. CONCLUSIONS

In this paper, an interleaved Fuel Cell based high step-down conversion ratio dcdc converter with low switch voltage stress has been proposed. In the proposed converter, two input capacitors are series-charged by the input voltage and parallel discharged by a new fourphase IBC for providing a much higher stepdown conversion ratio without adopting an extreme short duty cycle. Based on the capacitive voltage division, the main objectives of the new voltage divider circuit in the converter are both storing energy in the blocking capacitors for increasing the step-down conversion ratio and reducing voltage stresses of active switches. As a result, the proposed converter topology possesses the low switch voltage stress characteristic. This will allow one to choose lower voltage rating MOSFETs to reduce both switching and conduction losses.

Moreover, due to the charge balance of the blocking capacitor, the converter features automatic uniform current sharing characteristic of the interleaved phases without adding extra circuitry or complex control methods. The operation principles and relevant analysis of the proposed converter are presented in this paper.

7.REFERENCES

[1]. Chen-Feng Chuang, *Member, IEEE*, Ching-Tsai Pan, *Member, IEEE*, and Hao-Chien Cheng" A Novel Transformer less Interleaved Four-Phase Step-Down DC Converter With Low Switch Voltage Stress and Automatic Uniform Current-Sharing Characteristics" *IEEE Transactions On Power Electronics*, Vol. 31, No. 1, January 2016

[2]. D. D.-C. Lu and V. G. Agelidis, "Photovoltaic-battery-powered DC bus system for common portable electronic devices," *IEEE Trans. Power Electron.*, vol. 24, no. 3, pp. 849– 855, Mar. 2009.

[3]. K. Sun, L. Zhang, Y. Xing, and J. M. Guerrero, "A distributed control strategy based on DC bus signalling for modular photovoltaic generation systems with battery energy storage," *IEEE Trans. Ind. Electron.*, vol. 26, no. 10, pp. 3032–3045, Oct. 2010.

[4]. M. Pahlevaninezhad, J. Drobnik, P. K. Jain, and A. Bakhshai, "A load adaptive control approach for a zero-voltage-switching DC/DC converter used for electric vehicles," *IEEE*



Trans. Ind. Electron., vol. 59, no. 2, pp. 920–933, Feb. 2012.

[5]. X. Du and H. M. Tai, "Double-frequency buck converter," *IEEE Trans. .Ind. Electron.*, vol. 56, no. 54, pp. 1690–1698, May 2009.

[6]. X. Song, W. Siu-Chung, T. Siew-Chong, and C. K. Tse, "A family of exponential stepdown switched-capacitor converters and their applications in two-stage converters," *IEEE Trans. Power Electron.*, vol. 29, no. 4, pp. 1870–1880, Apr. 2014.

[7]. Y. Jang, M. M. Jovanovid, and Y. Panov, "Multiphase buck converters with extended duty cycle," in *Proc. IEEE Appl. Power Electron. Conf.*, Mar. 2006, pp. 38–44.

[8]. B. Oraw and R. Ayyanar, "Small signal modeling and control design for new extended duty ratio, interleaved multiphase synchronous buck converter," in *Proc. 28th Annu. Int. Telecommun. Energy Conf.*, Feb. 2006, pp. 1–8

[9]. K. Abe, K. Nishijima, K. Harada, T. Nakano, T. Nabeshima, and T. Sato, "A novel multi-phase buck converter for lap-top PC," in *Proc. Power Convers. Conf.*, Nagoya, Japan, Apr. 2007, pp. 885–891.

[10]. I. O. Lee, S. Y. Cho, and G.W. Moon, "Interleaved buck converter having low switching losses and improved step-down conversion ratio," *IEEE Trans. Power Electron.*, vol. 27, no. 8, pp. 3664–3675, Aug. 2012.

[11]. P. Xu, J. Wei, and F. C. Lee, "Multiphase coupled-buck converter—A novel high efficient

12 V voltage regulator module," *IEEE Trans.Power Electron.*, vol. 18, no. 1, pp. 74–82, Jan.2003.

[12]. R. Loera-Palomo, J. A. Morales-Saldaⁿa, and E. Palacios-Hern'andez, "Quadratic stepdown dc-dc converters based on reduced redundant power processing approach," *IET Power Electron.*, vol. 6, pp. 136–145, 2013.

AUTHOR DETAILS

BODISETTY RAMANJULU



Received B.Tech degree from SASTRA UNIVERSITY,Tirumalisamudram,Thanjavur-613401. And currently pursuing M.Tech in power electronics at Ellenki college of engineering & technology,Patelguda ,Ameenpur,Sanga reddy-502319, Telangana. His area of interest in Power electronic control of dc drives.He had an experience of 2years as a Teaching Asst.

A. RAVI KUMAR



obtained his BE (EEE) degree from Ellenki college of engineering & technology in 2009, M.Tech.(Power electronics) from Ellenki



college of eng & tech, Hyderabad in 2012.He working as Asst. Prof. in Ellenki college of eng & tech. His areas of interest include power system operation & control, distribution studies and optimization techniques in power system operation. He is having 5 years teaching experience.

D. PRASADA RAO



Obtained his BE (EEE) degree from SVH college of Engineering & technology in 2001, M.Tech.(Power Systems) from JNTUK, in 2009.He working as Asst. Prof. in Ellenki college of eng & tech. His areas of interest include power system Automation& Power system distribution. He is having 10 years teaching experience.