

Railway Track Crack Recogination and Data Examination

B. LAXMAN

Assistant Professor, Department of ECE Chaitanya Institute of Technology and Science, Warangal, Telangana

ABSTRACT

The main aim of this project is railway track crack detection system using an Internet of things like as data analysis and Railway track monitoring and detect the crack and Prevents the train accidents and saves peoples life .This project pertains to a process for monitoring the condition of rail on train tracks and more specifically has the object of the identification of defects detected by monitoring equipment on the tracks to be checked to allow maintenance crack to subsequently find these defects. When we give the supply to the device, each sensor will produce the signal related position with the rail.

I.INTRODUCTION

The project relates to the location of singular points in the automatic control of railway tracks. According to a possible embodiment, the railway carriage carrying the control equipments is provided with sensor orientated to detect the crack and magnetic penetration sensor used to detect the crack. Hall sensor is used to detect the flow of magnetic flux in magnetic penetration sensor and GPS will gives the related location This project pertains to a process for monitoring the condition of rail on train tracks and more specifically has the object of the identification of defects detected by monitoring equipment on the tracks to be checked to allow maintenance crews to subsequently find these defects. When we give the supply to the device, the magnetic penetration sensor will produces the mantic flux

II. LITERATURE SURVEY

The main objective of the track crack detection and health monitoring in base station between two signals any track are broken, cut the track, and any fault means signal is transmitted to signal engineer, because 5volt power will be passing to track This technique used only for base station. Microcontroller: ATmega162 the ATmega162 is a low-power CMOS 8-bit microcontroller based on the AVR enhanced RISC architecture. By executing powerful instructions in a single clock cycle, the ATmega162 achieves throughputs approaching 1 MIPS per MHz allowing the system designed to optimize power consumption versus processing speed.

The GPS is used to receive the position data from the vehicles and display on a digital map. It too will have the interface to the communication link. Enhanced features include video features, trace mode, history track, vehicle database, network support.



Oral communication through telephonic and telegraphic conversations.IR sensors are also used to identify the crack in the railway. LASER, proximity sensor and detectors are, use to satellite communication. No combined solution for collisions avoidance, derailment and railway gate control. In this process is high cost, difficult, time wastage

GPS MAGNETIC PENETRATION HALL SENSOR

BLOCK DIAGRAM

Things in IOT:

The "Things" in IOT usually refers to IOT devices which have unique identities and can perform remote sensing, actuating and monitoring capabilities. IOT devices can exchange data with other connected devices and applications (directly or indirectly), or collect data from other devices and process the data either locally or send the data to centralized servers or cloud-based application back-ends for processing the data, or perform some tasks locally and other tasks within the IOT infrastructure, based on temporal and space constraints

III. MODULE DESCRIPTION

GPS(GLOBALPOSITIONING SYSTEM) :

The Global Positioning System (GPS) is a radio based navigation system that gives three dimensional coverage of the Earth, 24 hours a day in any weather conditions throughout the world. The technology seems to be beneficiary to the GPS user community in terms of obtaining accurate data up to about 100 meters for navigation, metre-level for mapping, and down to millimetre level for geodetic positioning. The GPS technology has tremendous amount of applications in Geographical Information System (GIS) data collection, surveying, and mapping

NODE MCU:

ESP-12E Wi-Fi module is developed by Aithinker Team. core processor ESP8266 in smaller sizes of the module encapsulates Ten silica L106 integrates industry-leading ultra low power 32-bit MCU micro, with the 16-bit short mode, Clock speed support 80 MHz, 160 MHz, supports the RTOS, integrated Wi-Fi MAC/BB/RF/PA/LNA, onboard antenna. module supports The standard IEEE802.11 b/g/n agreement, complete TCP/IP protocol stack. Users can use the add modules to an existing device networking, or building a separate network controller. ESP8266 is high integration wireless SOCs, designed for space and constrained mobile power platform designers. It provides unsurpassed ability to embed Wi-Fi capabilities within other



systems, or to function as a standalone application, with the lowest cost, and minimal space requirement.



Flow chart





HALL SENSOR

The Hall Effect is the most common method of measuring magnetic field and the Hall Effect sensors are very popular and have many contemporary applications. For example, they can be found in vehicles as wheel speed sensors as well as crankshaft or camshaft position sensors. Also they are often used as switches, MEMS compasses, proximity sensors and so on.

IV. SOFTWARE DETAILS

Arduino IDE:

The Arduino Integrated Development Environment - or Arduino Software (IDE) - contains a text editor for writing code, a message area, a text console, a toolbar with buttons for common functions and a series of menus. It connects to the Arduino and Genuino hardware to upload programs and communicate with them.

Programs written using arduino software are called sketches. These sketches are written in the text editor and are saved with the file extension. The editor has features for cutting for searching text. The messages are gives feedback while saving and exporting and also displays errors. The console displays text output by arduino software including complete error messages and other information. The toolbar buttons allows you



Available at <u>https://edupediapublications.org/journals</u>

e-ISSN: 2348-6848 p-ISSN: 2348-795X Volume 04 Issue 06 May 2017

to verify and upload programs, create, open and save sketches.

V. RESULTS:



talvay Task Gask Der: x √ twe lite x	θ - σ \$
Admin Login	
Rainer George Password:	
Enter Password	
🔘 Type hore to search 🛛 🖓 🖸 🤻 😫 🙆 💭 🖨 🙆 👘	🖬 🔯 🧶 📚 🔯 💆 🔷 🖂 AllPM
ul - duestifilities x /) Brainey Tackey Leten x () PDF to Word Converter x New Teo x	θ -
	<u>.</u>
Railway Irack	
ALL MENUS	Hanny Inter
CASHEGARD Zaheden Delhi•	Nepal Stipite Units
CHURTS SUBAR Jopur	•Lucinew Tige •Guestati
NOTFICATIONS ab Emirates Karadh	•Alahabad Rangput
TRACKSECORDS Alignet	Ranchi• Bangradesh nazy B38 Naty B38 B/e
Oman Soul Amounts	-Outar and Maida
eo . Muntailleo	Myanmar
NUMOC HOINS	•Vieyawada Patheri Patheri
INVICE ENFLOYEES	OIKer manuarum
P* Bergaiuru•	•Cherman Pr Bangkok
polizión: (1),cip *	Su
🔿 Type hore to sourch 🛛 🕹 🗇 🗶 🤮 👼 🖨 🦉	🖬 🙆 😫 💆 🧧 🖉 🔷 🖓
arl - dramesh17290gmi: X X Bralvey Tacking Admin: X Bralvey Tacking Admin: X Bralvey Tacking Admin (Admin Cashboard)	θ -
Railway Track	
Railway Toak Cask Delector	
Senso	1 =
TRACKRECORDS Source: Smart	Bridge
NAGE TRAN HOUTES	
MANAGE TRAINS	
WWWGE EMPLOYEES	+ Sensor1
65	
0.23	
0 11:07:00 2017-09-06	11:09:00 2017-09-06 Histohem as
Т	
F	

Railway track crack detection and sensor graph analysis



Mul-draresh1729@gmi x 0	Railway 1 artbridg	izding Admin X FDF to Word Convert e.com/admin/TrackRecords	er - X Nev Tab X		θ	- 0 X	
Railway Track				ADMIN	LOGOUT		
ALL MENUS Dasheoard			List of Railway Track Crack Details				
CHARTS	S No	Subject	Location	Status	CreatedOn		
NOTIFICATIONS	1	Crack is Detected On (2017-09-06 11.09:09)	Professors Quarters, Amberpet, Hyderabad, Telangana 500007, India	CR4CK DETECTED	2017-09-06 11:09:09		
TRACKRECORDS	2	Crack is Detected On (2017-09-06 11:07:55)	IICT Colony, Tamaka, Secunderabad, Telangana, India	CR4CK DETECTED	2017-09-06 11:07:55		
MANAGE TRAIN ROUTES							
MANAGE TRAINS							
MANAGE EMPLOYEES							
B) Strattinge							
pdiždoc (1) zip ^						Show all X	
🗄 🜔 Type here to search		I 0 🗶 🤤	😫 🏮 🗧 🖨 📾 🌒 😫	s 👔 😒	^≣	9:19 PM 10/23/2017 🖣	

VI. CONCLUSION AND FUTURE SCOPE

This system involves instrumentation system for detecting the railway track crack detection when the crack detected. The detected data from sensors is continuously uploaded to the cloud hosted for railway track crack detection. This system also notification services enables for the employees. An electromagnetic system for rail detection and traction enhancement comprises, in a preferred embodiment, Wheel axles, wiring coils around the Wheel axles, respectively, and a power source coupled to the .Wiring coils for supplying power to produce electromagnetic flux. The Wiring coils produce opposite magnetic north and South Pole pairs on the axles.

REFERENCES

[1] A. L. Polivka and W. L. Matheson, "Automatic train control system and method", U.S. Patent No. 5828979, (2014) October 27.

[2] A. L. A. T. D. Ambegoda, W. T. S. D. Κ. Т. Hemachandra, T. Silva. N. Samarasinghe Τ. L. K. and A. Samarasinghe, "Centralized traffic controlling system for SriLanka railways", 4th International Conference on Information and Automation for **Sustainability** (ICIAFS08), Sri lanka, (2013) December 12-14.

[3]"Automatic railway track switching system"International Journal of Advanced Technology, vol. 54, (2014).

[4] F. R. L. Boylestad and L. Nashelsky, "railway crack detection using gpa technology", 9th edition, Prentice Hall, USA, (2012), pp. 196-199

[5] A..H. Cribbens, "Solid-state interlocking (SSI): an integrated electronic signaling system for mainline railways", IEE proceedings, vol. 134, part B, no. 3, () May, (2012)pp. 148-158.

[6] G. Dipoppa, G. D' Alessandro, R. Semprini and E. Tronci, "Integrating automatic verification of safety requirements in railway interlocking system design", The 6th IEEE International Symposium on High Assurance Systems Engineering (HASE'01), Washington, USA, (2011) October2-24.

[7] G. Tarnai, "Safety verification for train traffic control communications", IEEE journal on selected areas in communications, vol. sac-4, no. I, (2012) October, pp. 1118-1120.".