



## Implementation of Secure Sharing of Data for Dynamic Multi-Owner in Cloud

**Student: Sandhya Rani Vaidyawar (13H61D5827)**

**Guide: V. Rama Krishna**

**(Assistant Professor) CVSR ENGINEERING COLLEGE**

### Abstract—

*With the character of low maintenance, cloud computing provides an economical and efficient solution for sharing group resource among cloud users. Unfortunately, sharing data in a multi-owner manner while preserving data and identity privacy from an untrusted cloud is still a challenging issue, due to the frequent change of the membership. In this paper, we propose a secure multiowner data sharing scheme, named Mona, for dynamic groups in the cloud. By leveraging group signature and dynamic broadcast encryption techniques, any cloud user can anonymously share data with others. Meanwhile, the storage overhead and encryption computation cost of our scheme are independent with the number of revoked users. In addition, we analyze the security of our scheme with rigorous proofs, and demonstrate the efficiency of our scheme in experiments.*

**Index Terms**—Cloud computing; data sharing; privacy-preserving; access control; dynamic groups

### INTRODUCTION

CLOUD computing is recognized as an alternative to traditional information technology due to its intrinsic resource-sharing and low-maintenance characteristics. In cloud computing, the cloud service providers (CSPs), such as Amazon, are able to deliver various services to cloud users with the help of powerful datacenters. By migrating the local data management systems into cloud servers, users can enjoy high-quality services and save significant investments on their local infrastructures. One of the most fundamental services offered by cloud providers is data storage. Let us consider a practical data application. A company allows its staffs in the same group or department to store and share files in the cloud. By utilizing the cloud, the staffs can be completely released from the troublesome local data storage and maintenance. However, it also poses a significant risk to the confidentiality of those stored files. Specifically, the cloud servers managed by cloud providers are not fully trusted by users while the data files stored in the

cloud may be sensitive and confidential, such as business plans. To preserve data privacy, a basic solution is to encrypt data files, and then upload the encrypted data into the cloud. Unfortunately, designing an efficient and secure data sharing scheme for groups in the cloud is not an easy task due to the following challenging issues.

First, identity privacy is one of the most significant obstacles for the wide deployment of cloud computing. Without the guarantee of identity privacy, users may be unwilling to join in cloud computing systems because their real identities could be easily disclosed to cloud providers and attackers. On the other hand, unconditional identity privacy may incur the abuse of privacy. For example, a misbehaved staff can deceive others in the company by sharing false files without being traceable. Therefore, traceability, which enables the group manager (e.g., a company manager) to reveal the real identity of a user, is also highly desirable.

Second, it is highly recommended that any member in a group should be able to fully enjoy the data storing and sharing services provided by

the cloud, which is defined as the multiple-owner manner. Compared with the single-owner manner, where only the group manager can store and modify data in the cloud, the multiple-owner manner is more flexible in practical applications. More concretely, each user in the group is able to not only read data, but also modify his/ her part of data in the entire data file shared by the company. Last but not least, groups are normally dynamic in practice, e.g., new staff participation and current employee revocation in a company. The changes of membership make secure data sharing extremely difficult. On one hand, the anonymous system challenges new granted users to learn the content of data files stored before their participation, because it is impossible for new granted users to contact with anonymous data owners, and obtain the corresponding decryption keys. On the other hand, an efficient membership revocation mechanism without updating the secret keys of the remaining users is also desired to minimize the complexity of key management.

Several security schemes for data sharing on untrusted servers have been proposed. In these approaches, data owners store the encrypted data files in untrusted storage and distribute the corresponding decryption keys only to authorized users. Thus, unauthorized users as well as storage servers cannot learn the content of the data files because they have no knowledge of the decryption keys.

Our contributions. To solve the challenges presented above, we propose Mona, a secure multi-owner data sharing scheme for dynamic groups in the cloud. The main contributions of this paper include:

1. We propose a secure multi-owner data sharing scheme. It implies that any user in the group can securely share data with others by the untrusted cloud.
2. Our proposed scheme is able to support dynamic groups efficiently. Specifically, new granted users can directly decrypt data files

uploaded before their participation without contacting with data owners. User revocation can be easily achieved through a novel revocation list without updating the secret keys of the remaining users. The size and computation overhead of encryption are constant and independent with the number of revoked users.

3. We provide secure and privacy-preserving access control to users, which guarantees any member in a group to anonymously utilize the cloud resource. Moreover, the real identities of data owners can be revealed by the group manager when disputes occur.

4. We provide rigorous security analysis, and perform extensive simulations to demonstrate the efficiency of our scheme in terms of storage and computation overhead. We can observe that how to securely share data files in a multiple-owner manner for dynamic groups while preserving identity privacy from an untrusted cloud remains to be a challenging issue. In this paper, we propose a novel Mona protocol for secure data sharing in cloud computing. Compared with the existing works, Mona offers unique features as follows:

1. Any user in the group can store and share data files with others by the cloud.
2. The encryption complexity and size of ciphertexts are independent with the number of revoked users in the system.
3. User revocation can be achieved without updating the private keys of the remaining users.
4. A new user can directly decrypt the files stored in the cloud before his participation.

## System Model

We consider a cloud computing architecture by combining with an example that a company uses a cloud to enable its staffs in the same group or department to share files. The system model consists of three different entities: the cloud, a group manager (i.e., the company manager), and a large number of group members (i.e., the staffs) as illustrated.



Cloud is operated by CSPs and provides priced abundant storage services. However, the cloud is not fully trusted by users since the CSPs are very likely to be outside of the cloud users' trusted domain. Similar to , we assume that the cloud server is honest but curious. That is, the cloud server will not maliciously delete or modify user data due to the protection of data auditing schemes but will try to learn the content of the stored data and the identities of cloud users. Group manager takes charge of system parameter generation, user registration, user revocation, and revealing the real identity of a dispute data owner. In the given example, the group manager is acted by the administrator of the company.

Therefore, we assume that the group manager is fully trusted by the other parties. Group members are a set of registered users that will store their private data into the cloud server and share them with others in the group. In our example, the staffs play the role of group members. Note that, the group membership is dynamically changed, due to the staff resignation and new employee participation in the company.

**Anonymity and traceability:** Anonymity guarantees that group members can access the cloud without revealing the real identity. Although anonymity represents an effective protection for user identity, it also poses a potential inside attack risk to the system. For example, an inside attacker may store and share a mendacious information to derive substantial benefit. Thus, to tackle the inside attack, the group manager should have the ability to reveal the real identities of data owners.

**Efficiency:** The efficiency is defined as follows: Any group member can store and share data files with others in the group by the cloud . User revocation can be achieved without involving the remaining users. That is, the remaining users do not need to update their private keys or reencryption operations. New granted users can learn all the content data files stored before his

participation without contacting with the data owner.

## Client Computation Cost

We list the comparison on computation cost of clients for data generation operations between Mona and the way that directly using the original dynamic broadcast encryption (ODBE) [14]. It is easily observed that the computation cost in Mona is irrelevant to the number of revoked users. On the contrary, the computation cost increases with the number of revoked users in ODBE. The

reason is that the parameters  $\delta P_r$ ;  $ZrP$  can be obtained from the revocation list without sacrificing the security in Mona, while several time-consuming operations including point multiplications in  $G_1$  and exponentiations in  $G_2$  have to be performed by clients to compute the parameters in ODBE. From Figs. 2a and 2b, we can find out that sharing a 10-Mbyte file and a 100-Mbyte one, cost a client about 0.2 and 1.4 seconds in our scheme, respectively, which implies that the symmetrical encryption operation dominates the computation cost when the file is large.

## Cloud Computation Cost

To evaluate the performance of the cloud in Mona, we test its computation cost to respond various client operation requests including file generation, file access, and file deletion. Assuming the sizes of requested files are 100 and 10 MB, the test results are given in Table 3. It can be seen that the computation cost of the cloud is deemed acceptable, even when the number of revoked users is large. This is because the cloud only involves group signature and revocation verifications to ensure the validity of the requestor for all operations. In addition, it is worth noting that the computation cost is independent with the size of the requested file for access and deletion operations, since the size of signed message is constant, e.g.,  $\delta ID_{group}$ ;



IDdata; tP in file access and dIDdata; \_P in file deletion.

## CONCLUSION

In this paper, we design a secure data sharing scheme, Mona, for dynamic groups in an untrusted cloud. In Mona, a user is able to share data with others in the group without revealing identity privacy to the cloud. Additionally, Mona supports efficient user revocation and new user joining. More specially, efficient user revocation can be achieved through a public revocation list without updating the private keys of the remaining users, and new users can directly decrypt files stored in the cloud before their participation. Moreover, the storage overhead and the encryption computation cost are constant. Extensive analyses show that our proposed scheme satisfies the desired security requirements and guarantees efficiency as well.

## REFERENCES

[1] M. Armbrust, A. Fox, R. Griffith, A.D. Joseph, R.H. Katz, A. Konwinski, G. Lee, D.A. Patterson, A. Rabkin, I. Stoica, and M. Zaharia, "A View of Cloud Computing," *Comm. ACM*, vol. 53, no. 4, pp. 50-58, Apr. 2010.

[2] S. Kamara and K. Lauter, "Cryptographic Cloud Storage," *Proc. Int'l Conf. Financial Cryptography and Data Security (FC)*, pp. 136-149, Jan. 2010.

[3] S. Yu, C. Wang, K. Ren, and W. Lou, "Achieving Secure, Scalable, and Fine-Grained Data Access Control in Cloud Computing," *Proc. IEEE INFOCOM*, pp. 534-542, 2010.

[4] M. Kallahalla, E. Riedel, R. Swaminathan, Q. Wang, and K. Fu, "Plutus: Scalable Secure File Sharing on Untrusted Storage," *Proc. USENIX Conf. File and Storage Technologies*, pp. 29-42, 2003.

[5] E. Goh, H. Shacham, N. Modadugu, and D. Boneh, "Sirius: Securing Remote Untrusted Storage," *Proc. Network and Distributed Systems Security Symp. (NDSS)*, pp. 131-145, 2003.

[6] G. Ateniese, K. Fu, M. Green, and S. Hohenberger, "Improved Proxy Re-Encryption Schemes with Applications to Secure Distributed Storage," *Proc. Network and Distributed Systems Security Symp. (NDSS)*, pp. 29-43, 2005.